



exocet WINTERISED GAS OIL EXTRA

(XO1250GO)

DESCRIPTION

Exocet Winterised Gas Oil Extra combines the functions of Exocet Gas Oil Extra and Exocet Anti Wax into a single packaged additive.

APPLICATION

Exocet Winterised Gas Oil Extra is added to fuel at the rate of 1 litre of additive to 1,000 litres of fuel.

The additive will counter any negative effects resulting from the introduction of the latest gas oil specifications, notably the reduction in sulphur content and the increase in the allowable FAME (biodiesel) content.

Additionally, when used as a preventative, it will improve the cold flow and handling properties of diesel and gas oil. It is not a cure and will not work on already waxed fuel.

Typical applications are agricultural and horticultural machinery, construction equipment, airport vehicles and fork lift trucks.

The product is formulated from recognised fuel additive components and should not void an engine manufacturer's warranty. In fact, many engine manufacturers now recommend the use of upgrade additives when red/green diesel is used.

BENEFITS



FEATURES

INCREASED CETANE NUMBER

Benefits:

- Easier starting
- Increased pulling power
- Smoother power delivery
- Reduced visible emissions (smoke)
- Improved combustion efficiency
- Aligns with modern engine calibrations

INCREASED FUEL LUBRICITY

Benefits:

- Compensates for sulphur reduction
- Protects against premature wear in fuel pumps and fuel injectors
- Reduces friction

ENHANCED WATER RESISTANCE

Benefits:

- Prevents emulsions forming and resultant filter blockages
- Keeps water out of the fuel

ANTI WAXING PROPERTIES

Benefits:

- Boosts the fuel's resistance to waxing
- Allows operation at colder temperatures than fuel specification
- Inhibits the formation of wax crystals
- Reduces the potential for filter plugging
- Works with maximum allowable FAME contents

WHEN TO USE

- A combination product with the usage and benefits of both Anti Wax and Gas Oil Extra

TREATMENT RATIO

1 litre of additive treats 1,000 litres of fuel

All Exocet® branded products are available in a range of sizes to 1,000 litres

Head office: Fuel Additive Science Technologies Ltd, Unit 29 Atcham Business Park, Shrewsbury, Shropshire, SY4 4UG